SHARP

Be Original.

Engage Your Audience with around-the-clock Signage Solutions

The 55" Class **PN-VU551** LCD monitor is designed for ease of use and flexibility. Ideal for well-lit environments, this LCD monitor prevents the risk of any on-screen reflections and glare. With their outstanding image quality and 24/7 operation, this monitor can deliver an extraordinary performance either in landscape or portrait orientation.

OPS Support

PN-VU series offer compliance with OPS (Open Pluggable Standard). Offering enhanced processing power, OPS gives you the freedom to choose either Windows or Android* – whichever operating system best suits your specific application.

Embedded USB Media Player

The In-Built USB Media Player allows for Picture, Audio and Video content to be played directly from a USB and HTML5 Support.

24/7 Operation

PN-VU series are quality confirmed to operate 24 hours a day without any issues. Furthermore, these high quality screens come with brightness levels of 700 cd/m², which make them ideal for heavily lit environments.

Built-in Connectivity

PN-VU series features wired and wireless embedded WiFi connectivity.. Due to their wireless capabilities, the displays can easily gather content without any external device. Moreover, their WiFi connection enables you to use Miracast for screen sharing.

Specifications*

Model		PN-VU551
Installation		Portrait / Landscape
LCD Panel		55-inch
	Max. Resolution	1,920 x 1,080 pixels, Full HD
	Brightness	700 cd/m²
	Contrast Ratio	1,000 : 1
	Viewing Angle (H/V)	178°/178° (CR ≥ 10)
	Pixel Pitch	0.630 mm x 0.630 mm
	Display Colours	8bit, 16.7 M colors
	Screen Finish	Hard coating(3H), Anti-glare treatment
	Active Screen Area (W x H)	1209.60mm x 680.40mm
	Response Time	9 ms
	Backlight	Direct LED
OPS Slot		Ready
Input Terminals		HDMI 2.0 x 1 , DVI x 1 , VGA x 1, USB 2.0 x 2 , USB 3.0 x 1 , RS232C x 1, LAN x 1, IR Receiver x 1, RCA x 1, YPbPr x 1
Output Terminals		RCA L/R, 3.5 mm-diameter mini stereo jack x 1, SPDIF Coaxial
Network		RJ45, Wireless (2.4 GHz /5 GHz), Wi-Di, Miracast
Emebedded USB Player		YES (Supports Image , Audio, Video Files)
Built-in Speaker	Output Power	8 W + 8 W
Mounting		400 x 200 mm M6
Power Supply		110V – 240V AC, 50/60 Hz 1,300mA
Power Consumption		130 W
Environmental Conditions	Operating Temperature	0°C to 40°C
Dimensions (W x D x H) (approx.) (display only)		1238.20 x 103.80 x 711.80 mm
Weight (approx.)		17.5 kg
Accessories		Remote Control x 1, Remote Control Battery (AAA) x 2, IR Receiver Cable x 1, Power Cable (UK/EU) x 2, Cable management clips x 1, Wall mount adapter, Wall mount screws, VESA - bolt (M6 x 20mm) x 4, Owners Manual (English, Arabic, French, Russian), Wall mount Guide x 1

* Tentative. Design and specifications are subject to change without prior notice.

Dust Proof is not available on this product

DOLBY DIGITAL

HDMI™ HIGH-DEFINITION MULTIMEDIA INTERFACE

SHARP
Be Original.